

8515E Asphalt Paver

LeeBoy®



Sleek, modern and low-profile are three words that immediately come to mind when evaluating the LeeBoy 8515E Asphalt Paver. Featuring an engine hood height of 69 inches (1.75 m) and a sliding control station, the 8515E gives the operator an extremely clear and comfortable view of their surroundings. With a class-leading tunnel size and self cleaning conveyor bars, this machine is built to perform at the highest level. Easy-to-access, convenient maintenance areas are also a highlight of machine ownership.

Performance Features:

- 74 hp (48 kw) Kubota Tier 4 Final Diesel Engine
- Paving Widths Variable Up To 15'
- Low Profile Engine Hood For Better Visibility
- Choice of High Deck or Low Deck Configuration
- Sliding Operator Control Station
- Ultra-efficient Material Management System
- Pressure Ports for Diagnostics and Testing
- 7.5 Ton Capacity Material Hopper
- Proven Legend Screed System
- Electric Screed Heat, 10 kw Generator
- Heavy-duty Undercarriage and Track System



8515E Asphalt Paver Specifications



Dimensions	<ul style="list-style-type: none"> - Length: 13' 5" - Width: 8' 6" transport 10' hopper wings down - Height: 8' - Total Weight: 17,600 lbs. 	Steering	<ul style="list-style-type: none"> - Dual electronic steering controls - Electronically controlled pumps operated by the forward/reverse joysticks
Engine	Kubota turbocharged diesel, Tier 4 Final – 74 hp (55.4 kw)	Washdown System	Electric HD pump and two hose reels
Capacities	<ul style="list-style-type: none"> - Fuel: 19 gallons - Hydraulic reservoir: 19 gallons - Washdown tank: 7 gallons 	Push Rollers	Two vertically adjustable rollers with sealed bearings mounted to allow pivoting on frame
Hopper	Hopper size: 7.5 ton	Track Drive System	<ul style="list-style-type: none"> - Hydrostatically powered, self-cleaning crawler type - Track size: 14" wide x 77" long poly - Paving speed: 0 to 150' per minute (1.7 mph) - Travel speed: 0 to 300' per minute (3.4 mph)
Paving Widths	Variable up to 15'	Additional Standard Equipment	<ul style="list-style-type: none"> - Back-up alarm - LED beacon light - LED work light package - Vandalism protection covers - Electronic gauge package (oil pressure, hour meter, fuel gauge, volt meter, water temp, tachometer, hydraulic oil temp, level warning)
Paving Depths	<ul style="list-style-type: none"> - Manual flight screws positioned on the screed to control material thickness - Depth: 0" to 6" 	Optional Equipment	<ul style="list-style-type: none"> - Legend HD Screed, 8' to 15', 10kw generator - Remote screed control - Automatic screed temperature controls - Screed extension vibration - Rubber track, continuous - in lieu of poly - Steel track – in lieu of poly - Sloping screed extensions - Heated end gates - Truck hitch - Power crown - Steering wheel drive controls (in lieu of joysticks) - Wiring only, grade controls, includes A/M module - Sonic grade control both sides - Sonic grade control, one side (TopCon) - Dual sonic grade (Topcon) - Dual sonic grade and slope (Topcon) - 12" x 4.5" berm extension, left and right - Other options available
Screed	<ul style="list-style-type: none"> - Legend Electric screed - Consisting of a main screed and two hydraulically operated screed extensions - Equipped with two electric vibrators 		
Screed Heat	<ul style="list-style-type: none"> - Legend electric screed heat, 10kw generator - Electric timer and automatic RPM control system - 2 Blade heating elements in main, 1 blade element in each extension 		
Screed Crown/Valley	<ul style="list-style-type: none"> - Equipped with a crown/invert adjustment - Includes a leveling indicator for the operator 		
Material Handling	<ul style="list-style-type: none"> - Two independent hydraulically operated under auger material cutoffs - Two 12" independent hydraulically operated cast augers 		
Operator's Platform	<ul style="list-style-type: none"> - Full machine width platform - Walkboard extensions slide outs, left and right 		
Operator's Controls	All control switches are in a single control box which can be moved from right side to left side		



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com



LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-1008.12-EN